




## Product information M4-S-AC/DC 300W

Industrial Ethernet:Backbone Switches:Power supplies:M4-S-AC/DC 300W

<https://www.e-catalog.beldensolutions.com:443/link/57078-24455-49838-24531-39841/en/conf/ui/state>

Name	M4-S-AC/DC 300W
	
	Power supply for MACH 4002 switch chassis
<b>Delivery informations</b>	
Availability	available
<b>Product description</b>	
Description	Power supply for MACH 4002 switch chassis
Order No.	943 870-001
Type	M4-S-AC/DC 300W
<b>Service</b>	
Diagnostics	LEDs (P1) at basic device
<b>Current consumption</b>	
Activation current	typ. < 40 A at 265 V AC and cold start
<b>Technical data</b>	
Operating voltage	100-240 V AC
Operating temperature	0°C to +60°C
Input frequency	47-63 Hz
Nominal power of voltage supply	350 W (230 V), 370 W (110 V)
<b>Power requirements</b>	
Current consumption	1,8 A (230 V), 4,2 A (115V)
<b>More interfaces</b>	
Voltage input	Non-heating appliance socket
<b>Approvals</b>	
Safety of industrial control equipment	cUL 508
Safety of information technology equipment	cUL 60950-1
Shipbuilding	Germanischer Lloyd
<b>Scope of delivery and accessories</b>	
Scope of delivery	device, manual

For more information please contact:

**Hirschmann Automation and Control GmbH**

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: [inet-sales@belden.com](mailto:inet-sales@belden.com)

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.