




Product information Industrial HiVision - Industrial HiVision 6.0, 32 Nodes

Industrial Ethernet:Network Management:Industrial HiVision:Industrial HiVision

<https://www.e-catalog.beldensolutions.com:443/link/57078-24455-24540-24541-435520/en/IHV-032F06.0/uistate>

Name	Industrial HiVision
	
	Network management software for monitoring of industrial networks with up to 32 nodes (IP addresses).
Delivery informations	
Availability	available
Product description	
Description	Network management software for monitoring of industrial networks with up to 32 nodes (IP addresses).
Type	Industrial HiVision 6.0, 32 Nodes
Order No.	943 156-032
License	License enables supervision of up to 32 nodes (IP addresses).
Node extension	To increase the amount of supervised nodes, licenses can be combined.
Diagnostics	
Topology recognition	Topology recognition is based on LLDP (Link Layer Discovery Protocol, IEEE802.1AB) and Learned Address Tables. Switches, routers, WLAN devices, unmanaged switches/hubs, and end devices are supported. Can also map networks behind a router. Path Availability Calculation.
Monitoring	Graphical status representation for devices, links, power supplies, fans, and any other device sub-component. Status displays for third-party products. All statuses are configurable. Supports multiple topology windows and a network hierarchy view. User configurable event log. Customisable event actions. Reporting tool. Project setup wizard. Hierarchical supervision structure. Task scheduler.
Modules and components	MACH 4000/1000/100, GREYHOUND, MICE, PowerMICE, MSP, RSP, RS2, RED, EAGLE20, EAGLE30, EES, EESX, RS20/30/40, RSR, RSB, MICE20/30, OCTOPUS, LION, GigaLION, OpenBAT, BAT Controller, BAT54 Access Point and Client, BAT300, BAT-C, GECKO, SPIDER, any third-party SNMP capable device, any ICMP (Ping) capable device.
Event generation	polling and SNMPv1 trap support
Alarm and event actions	Alarm and event logging. Alarm actions such as message window, email, Push notifications, SMS and start executable. Event forwarding to Syslog server. Audible alarm.
SCADA /Process visualisation	
OPC Server	Map device and connection states as well as device properties. Can be used inside SCADA systems via the OPC Data Access 2.0/3.0 or OPC UA interface.
ActiveX Control	Graphical User Interface can be reused inside SCADA systems via an ActiveX control
Protocols	
Supported protocols	HiDiscovery, ICMP (Ping), SNMPv1, SNMPv3, OPC DA 2.0/3.0, OPC UA
Configuration	
Configuration functions	Individual device configuration. Configuration of multiple devices simultaneously. Configuration of identical parameters across multiple device types simultaneously. Firmware update of multiple devices. HiFusion for integration of third-party devices.
Documentation	
Documentation	documentation, export of maps and lists, inventory
Language Support	
Menus and dialogs	Chinese, English, French, German, Greek, Indonesian, Italian, Japanese, Korean, Portuguese, Russian, Spanish
Manual and help texts	Chinese, English, French, German, Italian, Spanish
Software requirements	
Operating system	Windows 7, Windows 8.1 (64 Bit), Windows Server 2008 R2, Windows Server 2012, PC Linux: 64 Bit: Kernel 2.6, glibc 2.4 (approved for Debian 7.6 and Red Hat 7.0)
Browser	Internet Explorer 4.0 or higher, Java runtime environment 1.5.0 is also installed
Hardware requirements	
Processor	x86 compatible CPU, min. 1 GHz
RAM	32 Bit: 2 GB minimum 64 Bit: 4 GB minimum
Hard disk space	2 GB free
Network	Ethernet network with TCP/IP protocol stack. Supports multiple network cards.
Scope of delivery and accessories	
Scope of delivery	printed manual (German and English), CD-ROM with multilingual product version, manual and form for licensing.



HIRSCHMANN

A BELDEN BRAND

Industrial Ethernet:Network Management:Industrial HiVision:Industrial HiVision

<https://www.e-catalog.beldensolutions.com:443/link/57078-24455-24540-24541-435520/en/HHV-032F06.0/ui/state>

Product variants

Version + Nodes	
	Full version - 32 nodes.

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.